

CLEAN VERSIONS OF AMENDED CLAIMS ONLY

For ease of reference, Applicant provides clean versions of amended claims 2 and 13:

2. A disposable lighter, comprising:

a lighter body;

a mounting frame, which is sealedly affixed on top of said lighter body, comprising a first and a second supporting wall upwardly extended from two sides of said mounting frame;

an ignition device comprising a flint and a striking wheel, said striking wheel having a circumferential coarse striking surface and rotatably mounted between said first and second supporting walls, wherein said striking wheel further comprising two circular discs located at two sides of said striking surface, each of said circular discs having a glossy circumferential surface and positioned within each of two gaps formed between said first and second supporting walls and said striking wheel; and

a U-shaped wind shield mounted on said first and second supporting walls, said wind shield having an all around vertical U-shaped side wall which has a round end portion and two wing portions extending from said round end portion, a top wall horizontally and inwardly extending from a top side of said round end portion of said U-shaped side wall and defining a cutout, and a first and a second L-shaped bent-edge members respectively extended from said top wall along said top side and said end side of each of said wing portions for fittedly and respectively resting on said first and second supporting walls, a top end corner of each of said wing portions forming a curved corner which has a curvature matching with at least a quarter of a circumference of said striking wheel;

wherein each of said circular discs has a diameter approximately equal to that of said striking wheel.

13. A disposable lighter, comprising:

a lighter body for receiving a liquefied fuel therein;

a mounting frame, which is sealedly affixed on top of said lighter body, comprising a first and a second supporting wall upwardly extended from two sides of said mounting frame, said mounting frame further having a vertical spring chamber between said first and second supporting walls;

a flint spring being received in said spring chamber;

a gas lever being pivotally mounted between said first and second supporting walls;

a gas valve with a gas nozzle, said gas nozzle being engaged with an end of said gas lever to permit release of gas from an interior of said lighter body via said gas valve;

an ignition device comprising a flint and a striking wheel, said striking wheel having a circumferential coarse striking surface being positioned right above and in contact with said flint and rotatably mounting between said first and second supporting walls, wherein said striking wheel further comprising two circular discs located at two sides of said striking surface, each of said circular discs having a glossy circumferential surface and positioned within each of two gaps formed between said first and second supporting walls and said striking wheel; and

a U-shaped wind shield extends over said first and second supporting walls to cover said gas nozzle and said first and second supporting walls, said wind shield having an all around vertical U-shaped side wall which has a round end portion and two wing portions extending from said round end portion, and a first and a second L-shaped bent-edge members which are

respectively and perpendicularly bent from a top side and an end side of said wing portions, said striking surface at an elevation lower than said bent-edge members, wherein said first and second bent-edge members are respectively extended from a top wall along said top side and said end side of each of said wing portions, a top end corner of each of said wing portions forming a curved corner which has a curvature matching with at least a quarter of a circumference of said striking wheel;

wherein each of said circular discs has a diameter approximately equal to that of said striking wheel.